

TECHNICAL SPECIFICATIONS NEO1 HOSES



5m	green	2600.3005.RQ
	blue	2600.3205.RQ
	red	2600.3405.RQ
10m	green	2600.3010.RQ
	blue	2600.3210.RQ
	red	2600.3410.RQ
15m	green	2600.3015.RQ
	blue	2600.3215.RQ
	red	2600.3415.RQ

NEO1 HOSES

neo1
TECHNOLOGY

Nominal pressure Inner feed hose	UltimatePressure™ 350 Bar
Nominal pressure Outer return hose	20 Bar
Safety factor	4:1 for hose assembly
Temperature range	-20° +55° C
EN 13204	Compliant
NFPA 1936	Compliant
Bend radius	50 mm
Bend restrictor/hosegrip	Yes
Automatic by-pass	Yes
Built-in Pressure Release	Yes
Coaxial hose & coupling	Yes
Flat-face	Yes
Connect/disconnect under free-flow pressure	Yes
Rotates/swivels when connected	Yes
Hosestrap/loop binder	Yes
Dustcaps	Yes
Weight (5m / 10m / 15m)	3,3 kg / 5.6 kg / 7.9 kg

ACCESSORIES

Hosestrap/loop binder	2600.0000
-----------------------	-----------



Information contained in this document is believed to be accurate. However RESQTEC does not guarantee the completeness or accuracy of any of the published information.



RESQTEC Zumro B.V.
Meer en Duin 82 | 2163 HC Lisse, the Netherlands

T +31 (0)252 419002
E info@resqtec.com

F +31 (0)252 411794
W www.resqtec.com

RESQTEC®